

MC420S Mancooler

Specifications:

- 115V, 1 HP, 1 Phase, 2 Speed
- Rocker switch
- Steel hubbed wheels
- Motor out of air stream - Stays clean
- Aluminum four bladed propeller
- Full Width Easy Grip Handle

- Quiet Operation
- DbA: High 75, Low 67
- Fully Assembled
- 2 Year Warranty

Performance 115V

PROP DIA.	CFM		RPM		
	High	Low	High	Low	HP
42"	17000	9500	430	285	1



MC420S



I-18TELS Low Stand Fan

Specifications:

- 115V, 1 Phase, 3 Speed, Totally Enclosed, Ball Bearing Motor
- Adjusts 360°
- Nickel Chrome Guards

- Meets OSHA Regulations
- Aluminum Propellers
- Chrome Yoke Mount Included
- 1 Year Warranty

Performance 115V

PROP DIA.	CFM			RPM			F.L. Amps
	High	Med	Low	High	Med	Low	
18"	4550	3824	3346	1600	1350	1180	1.65



I-18TELS

CA30APE Commercial Air Circulator

Specifications:

- Non-oscillating, 1/4 HP, 3 speed, 115V, 1 Phase, TEAO motor
- 30 In. galvanized steel propeller
- Pedestal adjusts 43 - 63 In.
- 15 ft. supply cord/plug
- Unit pack includes motor, pedestal, base, guards propeller shipped in one box
- 3.5 F.L. amps
- 2 Year Warranty

Performance 115V

PROP DIA.	CFM			RPM			HP	F.L. Amps
	High	Med	Low	High	Med	Low		
30"	6100	4400	2700	1100	800	600	1/4	3.5



CA30APE